

MTS-200 AUTOMATED TRANSMISSION SYSTEM



A maximum of 16 languages audio contents can be played simultaneously. With **okayo** MTS-200 audio player, organizers can easily plan tour routes with software or GPS positioning function. Everything comes neatly packed in a flight case for mobility and quick installation. Operating with an external antenna, DPA-12, transmission range can exceed 100 meters or more. In-ear monitoring controls audio commentaries in an efficiency way.

All **okayo** tour guide systems, such as WT-808, WT-300, WT-500, EJ-5 and EJ-7 are compatible with MTS-200.

Features:

- 16 languages in transmission concurrently.
- 100 to 300 meters coverage.
- Individual monitor for each language.
- Voice override and broadcast.
- Supports GPS solution (optional).
- Easy management – all in a case.





vessel



train



bus



GPS



16 language



MTS-200 OVERALL SYSTEM

Audio format	High quality MP3 audio compression
Bandwidth	50 Hz ~ 18 kHz
Dynamic range	95 dB
Storage supports	SD card
File format	FAT-12 / FAT-16 / FAT-32
Input supports	Aux in (RCA), Mic in (6.5 mm)
Output ports	8 channels (RCA), Mic in (6.5 mm)
Power requirements	100 ~ 240 VAC / 12 VDC, 2 A switching power supply
Dimensions (D x W x H)	210 x 430 x 44 (mm)
Weight	2.4 kg

AB-771T

Max. RF input power	17 dBm
RF output power (EU)	16 ± 1 dBm ; with EJ-774T (low power)
RF output power (NA)	< 22 dBm
Gain	10 dB
Input signal indicator threshold	> 5 dBm
In/Out impedance	50 Ω
Antenna connector	TNC female connector
Power requirements	100 ~ 240 V AC switching adapter 12 V DC
Dimensions (D x W x H)	205 x 215 x 44 (mm)
Weight	1.2 kg