

CHARGERS FOR TOUR GUIDE SYSTEM



Model name	HDC-502	HDC-502s	HDC-707	HDC-808	HDC-712	HDC-812
Slot	Dual slot	Dual slot	Dual slot		12-slot	
WT-300 series						
WT-500 series		✓				
WT-600 series		✓				
WT-808 series				✓		✓
DigiBee series		✓				
EJ-5 series	✓					
EJ-7 series			✓		✓	
Power requirements	AC 100 ~ 240 V, 50 / 60 Hz 5 V DC / 1 A	AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 1 A	AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 500 mA		AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 5 A	
Dimensions (D x W x H)	120 x 120 x 52 (mm)	120 x 120 x 52 (mm)	106 x 84 x 72 (mm)		330 x 310 x 165 (mm)	
Weight	174 g	174 g	160 g		4.5 kg	



Model name	HDC-312	HDC-300	HDC-324	HDC-525
Slot	12-slot	24-slot	24-slot	25-slot
WT-300 series	✓	✓		
WT-350 series			✓	
WT-500 series				✓
WT-600 series				✓
DigiBee series				✓
Power requirements	AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 5 A	AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 5 A	AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 5 A	AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 5 A
Dimensions (D x W x H)	340 x 157 x 88 (mm)	450 x 300 x 170 (mm)	445 x 275 x 175 (mm)	445 x 275 x 175 (mm)
Weight	1.54 kg	5.60 kg	5.10 kg	5.3 kg

CHARGERS FOR TOUR GUIDE SYSTEM



Model name	HDC-550	HDC-550+	HDC-520	HDC-530
Slot	50-slot	50-slot	20-slot	30-slot
WT-500 series	✓	✓		
WT-600 series	✓	✓		
DigiBee series	✓	✓		
EJ-5 series			✓	✓
Power requirements	AC 100 ~ 240 V, 50 / 60 Hz 185 W	AC 100 ~ 240 V, 50 / 60 Hz 185 W	AC 100 ~ 240 V, 50 / 60 Hz 200 W	AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 7 A
Dimensions (D x W x H)	339 x 482 x 211 (mm)	339 x 482 x 211 (mm)	484 x 169 x 239 (mm)	681 x 295 x 207 (mm)
Weight	12 kg	12 kg	4.7 kg	8 kg



Model name	HDC-36	HDC-736	HDC-50	HDC-750
Slot	36-slot		50-slot	
WT-808 series	✓		✓	
EJ-7 series		✓		✓
Power requirements	AC 100 ~ 240 V, 50 / 60 Hz 12 V DC / 7 A		AC 100 ~ 240 V, 50 / 60 Hz 250 W	
Dimensions (D x W x H)	870 x 370 x 205 (mm)		827 x 626 x 192 (mm) (HDC-50)	
Weight	9.6 kg		36 kg	