



# CHARGERS FOR TOUR GUIDE SYSTEM



|                        |   |   |                                     |
|------------------------|---|---|-------------------------------------|
| Model name             | <b>ATC-110</b>                              | <b>ATC-110U</b>                             | <b>ATC-150</b>                      |
| Item                   | 10-slot charger                             | 10-slot charger & uploader                  | 50-slot charger                     |
| AT-100                 | ✓   | ✓   | ✓                                   |
| Power requirements     | AC 100 ~ 240 V, 50 / 60 HZ<br>12 V DC / 5 A | AC 100 ~ 240 V, 50 / 60 HZ<br>12 V DC / 5 A | AC 100 ~ 240 V, 50 / 60 Hz<br>250 W |
| Dimensions (D x W x H) | 550 x 110 x 95 (mm)                         | 550 x 110 x 95 (mm)                         | 693 x 630 x 165 (mm)                |
| Weight                 | 2.5 kg                                      | 2.6 kg                                      | 22 kg                               |



|                        |                                     |                                     |                                     |   |
|------------------------|-------------------------------------|-------------------------------------|-------------------------------------|---|
| Model name             | <b>ATC-210</b>                      | <b>ATC-210U</b>                     | <b>ATC-220</b>                      | <b>ATC-221U</b>                             |
| Item                   | 10-slot charger                     | 10-slot charger and uploader        | 20-slot charger                     | 20-slot uploader                            |
| AT-200                 | ✓                                   | ✓                                   | ✓                                   | ✓   |
| AT-300                 | ✓                                   | ✓                                   | ✓                                   | ✓   |
| AT-500                 |                                     |                                     |                                     |   |
| Power requirements     | AC 100 ~ 240 V, 50 / 60 HZ<br>100 W | AC 100 ~ 240 V, 50 / 60 HZ<br>200 W | AC 100 ~ 240 V, 50 / 60 HZ<br>200 W | AC 100 ~ 240 V, 50 / 60 HZ<br>12 V DC / 5 A |
| Dimensions (D x W x H) | 237 x 482 x 88 (mm)                 | 237 x 482 x 88 (mm)                 | 237 x 482 x 177 (mm)                | 425 x 306 x 165 (mm)                        |
| Weight                 | 4.6 kg                              | 3.6 kg                              | 5.1 kg                              | 6.7 kg                                      |

• All specifications are subject to change.



# CHARGERS FOR TOUR GUIDE SYSTEM



|                        |                                     |
|------------------------|-------------------------------------|
| Model name             | <b>ATC-524</b>                      |
| Item                   | 24-slot wireless charger            |
| AT-500                 | ✓                                   |
| Power requirements     | AC 100 ~ 240 V, 50 / 60 Hz<br>250 W |
| Dimensions (D x W x H) | 254mm x 482mm x 220.5mm             |
| Weight                 | 8 kg                                |

|                        |                                     |
|------------------------|-------------------------------------|
| Model name             | <b>ATC-524U</b>                     |
| Item                   | 24-slot wireless charger & uploader |
| AT-500                 | ✓                                   |
| Power requirements     | AC 100 ~ 240 V, 50 / 60 Hz<br>250 W |
| Dimensions (D x W x H) | 254mm x 482mm x 220.5mm             |
| Weight                 | 8 kg                                |